

AMENDMENT TO THE CLAIMS

1-19. (canceled)

20. (previously presented) A light projection television using a scanning area light source, comprising an area light source unit, an image combination unit and an image unit, wherein

the area light source unit is used for projecting three light beams of R, G and B onto a rotating polygon mirror rotating at high speed, rotating polygon mirror is used for horizontally scanning the light beam to generate a horizontal line, vertically scanning the light beam line by line, repeating above 2-D scanning so as to transforming three light beams into an uniform scanning area having no interference and refreshing with a predetermined field frequency, and illuminating three spatial light modulators of R, G and B;

the image combination unit is used for combining three monochromatic images into a color image, wherein three spatial light modulators illuminated by three monochromatic light beams of R, G and B form three channel monochromatic images, which are combined in a combination prism to generate a color image;

the imaging unit is used for projecting the color image from the combination prism on a screen via an objective lens by taking the color image as an object of the objective lens.

21. (previously presented) The light projection television as

claimed in claim 20, wherein

said area light source unit comprises a red light emitter, a green light emitter, a blue light emitter, a rotating polygon mirror, a central rotation axis of the rotating polygon mirror, plane mirrors S at the side of the rotating polygon mirror and mirrors.

22. (previously presented) The light projection television as claimed in claim 20, wherein said image combination unit comprises a red channel 2-D spatial light modulator, a green channel 2-D spatial light modulator, a blue channel 2-D spatial light modulator and a combination prism.

23. (previously presented) The light projection television as claimed in claim 20, wherein said imaging unit comprises a projection objective and a screen.

24. (previously presented) The light projection television as claimed in claim 21, wherein said rotating polygon mirror is arranged properly in the path constituted of the green channel spatial light modulator, the combination prism and the projection objective, and can rotate about its own rotation axis, three light beams emitted from the red light emitter, the green light emitter and the blue light emitter irradiate onto the same plane mirror (S) of the rotating polygon mirror, and then reflected

back from the surface, the mirror is arranged in the path of red light beam from the red light emitter, the optical axis of beam reflected from the mirror points to the center of the red channel 2-D spatial light modulator, the aperture area of beam reflected from the mirror occupies the operating area of the red channel 2-D spatial light modulator, the mirror is arranged in reflecting blue light path of the blue light emitter, the optical axis of the beam of the blue channel 2-D spatial light modulator and the aperture area of beam reflected from the plane mirror occupies the operating area of the blue channel 2-D spatial light modulator, a green beam emitted directly from the plane mirror (S) of the rotating polygon mirror to the green channel 2-D spatial light modulator and aperture area of the green beam reflected from the plane mirror occupies operating area of the green channel 2-D spatial light modulator, three operating areas of the red channel 2-D spatial light modulator, the green channel 2-D spatial light modulator and the blue channel 2-D spatial light modulator are parallel to the corresponding operating areas of the combination prism.

25. (previously presented) The light projection television as claimed in claim 23, wherein said screen is arranged on the image plane of the projection objective, the object plane of the projection objective coincides with exiting beam combined by the combination prism.

26. (previously presented) The light projection television as claimed in claim 24, wherein each plane mirror (S) at the side of the rotating polygon mirror with respect to the direction of rotating axis makes a slope angle, the slope angles of the plane mirrors (S) corresponding to two ends of the diameters of the rotating polygon mirror are distributed uniformly in equal difference, the slope angle made by the surface of the first plane mirror (S) at the side of the rotating polygon mirror with respect to the direction of the rotating axis equals to zero, the diameter of the rotating polygon mirror through axis center of the rotating axis is perpendicular to the plane mirror (S) and pass through the center of the plane mirror, the diameter of the rotating polygon mirror are divided into the left and right parts which are symmetric each other about the diameter of the rotating polygon mirror, and the plane mirrors (S) at the left and right sides of the rotating polygon mirror are symmetric about the diameter, the plane mirrors of the rotating polygon mirror are arranged in equal angle difference of the slope angles of the adjacent plane mirrors with respect to the direction of the rotating axis, the number of the plane mirrors at the side of the rotating polygon mirror is even, N plane mirrors (S) are assumed and arranged clockwise from the first surface and then the slope angle of the first surface equals to zero, the slope angles of adjacent surfaces of two plane mirrors (S) from the second surface to the $(N/2)^{th}$ surface increase the same angle value progressively in turn, the slope angles of adjacent two surface of two plane mirrors from the $(N/2+1)^{th}$ surface to the $(N-1)^{th}$ surface decrease the same angle value progressively in turn.

27. (new) The light projection television as claimed in claim 20, wherein the scanning area light source, comprising of a light emitter and a rotating polygon mirror, and wherein,

said light emitter is used for emitting a light beam and projecting it onto said rotating polygon;
said rotating polygon mirror is used for horizontally scanning the light beam to generate a horizontal line, vertically scanning the light beam line by line, and repeating above 2-D scanning to form an uniform scanning area having no interference.

28.(new) The light projection television as claimed in claim 27, wherein a reflection surface of each plane mirror (S) at the side of the rotating polygon mirror has a slope angle with respect to the direction of self-rotating axis (AX2), a beam reflected from each plane mirror scans a line, and when rotating over one plane next plane mirror scans another line which is moved downward by one line to implement a 2-D scanning area.

29. (new) The scanning area light source as claimed in claim 28, wherein said rotating polygon mirror rotating at high speed is a symmetric polygon about the center of axis (AX2), each plane mirror (S) reflects light beams irradiated, reflection surfaces of the adjacent plane mirrors (S) have a slope angle with respect to axial direction each other.

30. (new) The scanning area light source as claimed in claim 29, wherein the rotating polygon mirror has N (N is a positive even number) plane mirrors (S) at the side of it and these plane mirrors (S) are symmetric about the center of the rotating polygon mirror, during scanning, in the 1-(N/2)th plane mirrors (S), the surface of each plane mirror (S) increase a same angle one by one with respect to the direction of the axis (AX2), from the (N/2+1)th plane mirror in the (N/2+1)-N/2 plane mirrors (S), each plane mirror (S) decreases the same angle one by one, the plane mirrors are arranged in symmetric on the left and right,

during $1-N/2$ plane mirrors (S) of the rotating polygon mirror scanning, each plane mirror (S) rotates over its surface, the scanning line moves an angle, and the scanning line moves downward by a line corresponding to the angle, when rotating over the $(N/2)$ th surface, the scanning line moves downward by $N/2$ lines in total, from the $(N/2+1)$ th line, every time rotating over one plane mirror (S), the scanning line moves upward one line until the N th line, the rotating polygon mirror rotates each circle to complete scanning up and down reciprocately one time.

31. (new) The scanning area light source as claimed in any one of claim 28 wherein overlapping degree of two adjacent scanning lines depends on the distance between the rotating polygon mirror and a screen, and on the size of cross section of scanning beam, and also on the size of slope angle of the surface of each plane mirror (S).